

# **GPZ 1000** - Next Generation UTM Appliances

October 2012

GPZ 1000 Next Generation UTM Appliances have extensive features including VLAN, Layer-8 technology, single sign-on, bridging, VPN SSL via x.509 certificates & VPN IPSec, IDS/ IPS, traffic shaping, antivirus, zero hour mail protection, web filtering as well as Application Control and the very latest procedure-oriented eGUI® technology.

Thanks to its hardware RAID (hot swap), 24/7 server hard disks, redundant power supply, and the high-performance HA mode, this appliance is 99.97% failsafe. The GPZ 1000 also features SFP ports, e.g. for OWG/optical fiber connections.





Specifications	GPZ 1000
Interfaces	
1 GbE Ports	2xRJ45 Intel 82576 (rear), 8x RJ45 Intel 82580EB (front)
SFP (Mini GBIC) Ports	4x SFP Intel 82576EB (front)
Redundant - HDD (Raid)	Yes
IPMI - Remote management	Yes
System Performance*	
Firewall throughput (Mbps)	7 500
VPN IPSec throughput (Mbps)	2 000
UTM throughput (Mbps)	1 000
IDS/IPS throughput (Mbps)	1 500
Concurrent sessions	2 000 000
New sessions pr. Second	25 000
Dimensions	
H x W x D (mms)	88 x 430 x 633
H x W x D (mms) - Packaging	223 x 567 x 793
Gross Weights (kgs)	арр. 18
Power	
Input Voltage (V)	AC 100-240
Redundant Power Supply	600 W
Environmental	
Operating Temperature (°C)	10 ~ 40
Storage Temperature (°C)	-40 ~ 65
Relative Humidity (Non condensing)	10 ~ 85%

\* System performance depends on activated proxies, IDS, application level and number of active VPN connections. We do not offer an express or implied warranty for the correctness /up-to-dateness of the information contained here (which may be change at any time). Future products or functions will be made available at the appropriate time.

©2012 gateProtect AG Germany. All rights reserved.

F© (€



**Hardware Certification** 

gateprotect AG Germany is one of the world's leading producers of IT-security solutions for effective network security. Our primary products are Next Generation Firewalls and Managed Security Systems. They protect small to large companies, nonprofit organisations and government networks from threats and attacks coming from the Internet.

gateprotects IT security solutions are used on the whole globe. The confidence in gateprotect is now demonstrated through 40,000 installations worldwide at client sites of all industries. Its UTM firewalls are listed in the "Magic Quadrant" of the international renowned market research company Gartner. Gartner only positions companies in its Magic Quadrant that meet their ambitious criteria, which include technological performance, a certain level of annual revenue and active customer references as well as the necessary functionality.

gateProtect AG Germany

Phone +49 (0) 40 278 850

Internet

www.gateprotect.com



# Feature overview - Next Generation UTM Appliances

September 2012

The "Next Generation UTM Appliances" from gateprotect are characterized by optimal scalability, security and performance. Thanks to a unique and patented eGUI® Technology, gateProtect sets standards when it comes to the configuration of modern security systems.

gateprotect's eGUI® Technology raises operating security and efficiency to a previously unattained level. Furthermore, gateprotect is the only manufacturer worldwide to implement the ISO NORM 9241 standard. gateprotect was recently honored with the Frost & Sullivan Best Practices Award 2011.



"The gateprotect ergonomic graphical user interface (eGUI) provides the most intuitive and effective visual UTM management interface available in the marketplace."











# Feature Specifications

### Firewall with DPI

- Stateful inspection Connection-tracking TCP/UDP/ICMP SPI and proxy combinable
- Gri and proxy combinable
  Time controlled firewall rules,
  content filter and internet connection
  IP-ranges, IP-groups
  Layer7-filter\*

- Deep packet inspection\* for application based blacklists over 600 apps supported

- Self- and predefined ports Supported protocols: TCP, UDP, ICMP, GRE, ESP, AH

### Management

- eGUI Technology
  -ISO 9241 compliant
  -immediate visual feedback for each setting
- self-explanatory functions
   overview of all active services
   overview of the whole network
   Layer and zoom function
- Languages: English, German, French, Italian,Spanish, Turkish Role-based firewall administration Role-based statistic-client

- SSH-CLL
- SSH-ULI Desktop configuration saved / restored separately from backup CLI on serial line Object oriented firewall configuration Direct Client Update function

### LAN / WAN-support

- Ethernet 10/100/1 000\*/10 000\* Mbit/s Twisted-Pair / Fibre-Optics MTU changeable (Ethernet/DSL)

- PPP-PAP, PPP-CHAP authentication
- Inactivity timeout
  Forced disconnect time
- Cablemodem, xDSL Concurrent connections
- Backup-connections

- Backup-connections
  Connection availability check
  Loadbalancing
  Time controlled internet connections
  Manual and automatic DNS assignment
  Multiple dyn-DNS support
  Supports 8 different dyn-DNS-services
  Source based routing
  Routing protocols RIP, OSPF

# ▶ User authentication

- Active Directory supported
- Active Directory groups integration OpenLDAP supported Local userdatabase
- Web-interface authentication
- (port changeable) Windows-client authentication
- Authentication on domain login Single sign on with Kerberos Single- and multi login

- Web-Landing-Page Login and logoff auditing User- and group statistics

- DHCP-relay DHCP-client
- DHCP-server (dynamic and fixed IP)

- Port forwarding
- PAT Dedicated DMZ-links
- DMZ-wizard
- Proxy supported (SMTP)\*

- Max. 4094 VLAN per interface possible 802.1q ethernet header tagging Combinable with bridging

- OSI-layer 2 firewall-function

- Spanning tree (bride-ID, port-cost) Unlimited bridges Unlimited interfaces per bridge Combinable with VPN-SSL

- Up- and download shapeable
- Multiple internet connection separately shapeable
- All services separately shapeable
- Maximum and guaranteed bandwidth adjustable
  QoS with TOS-flags supported
  QoS inside VPN connection supported

### ▶ High availability

- Active-passive HA
- Synchronisation on single / multiple dedicated links
- Manually switch roles

- Remote backup creation Small backup files Remote backup restore Restore backup on installation Automatic and time based creation of backups
- Automatic upload of backups on FTPor SCP-Server Auto-install-USB-stick with backup
- integrated

- SNMPv2c SNMP-traps
- Auditing of:
- CPU / Memory HDD / RAID
- Ethernet-interfaces Internet-connections
- VPN-tunnel
- Users Statistics, Updates
- DHCP

### ▶ Proxies¹

- HTTP (transparent or intransparent) HTTPS (available GPA 250 and higher)
- Support for Radius-server, AD-server, local user-database FTP,POP3,SMTP,SIP
- Integrated URL-/ content-filter
  Integrated antivirus-filter
  Integrated spam-filter
- Time-controlled

### ▶ Web-filter\*

- URL-filter with safe search enforcement
- Content-filter
  Block rules up to user-level
- Black-/ white-lists Im- / export of URL-lists File-extension blocking
- File-extension blocking Category-based website-blocking Self definable categories Scan-technology with online-database Transparent HTTP-proxy support Intransparent HTTP-proxy support

▶ Antivirus

Manual and automatic updates

- HTTP, HTTPS, FTP, POP3, SMTP Scans compressed data and archives Scans ISO 9660-files
- Exceptions definable

- ▶ Antispam\*
  - Online-scanner Scan-level adjustable

  - Real-time-detection-center
    Black- / white-email-sender-lists
    Mail-filter

    - Black / white-email-recipients-lists Automatically reject emails Automatically delete emails
- AD-email-addresses import

- ▶ IDS/IPS®
- Snort scan-engine 5000+ IDS-pattern Individual custom rules
- Security-level adjustable Rule groups selectable Exceptions definable
- Scanning of all interfaces Email on IDS events DoS, portscan protection
- Invalid network packet protection

- **▶** Monitoring\*
  - System-Info
- CPU- / memory usage Long-term-statistic HDD-status (partitions, usage, RAID)
- Network status (interfaces, routing, traffic,
- Process-monitoring VPN-monitoring User-authentication-monitoring

# Logging, Reporting\*

- Email notification
- Email notification Logging to multiple syslog-servers Categorized messages Report in admin-client (with filter) Export report to CSV-files

- ▶ Statistics<sup>3</sup>
- IP and IP-group statistic Separate services
- Single user / groups TOP-lists (surfcontrol) IDS-statistics
- Traffic-statistics
- AppFilter traffic statistics Antivirus- / antispam-statistics
  - Defence statistics Export statistic to CSV-files

- **▶ VPN**
- VPN-wizard Certificate-wizard
- Site-to-site
- Client-to-Site (Road warrior) Tunnel-Mode
- IKEv1, IKEv2
- PSK X.509-certificates
- 3DES, AES (128, 192, 256) Blowfish (128, 192, 256) DPD (Dead Peer Detection) NAT-T
- Compression
- Compression
  PFS (Perfect Forward Secrecy)
  MD5, SHA1, SHA2 (256, 384, 512)
  Diffi Hellman group
  (1, 2, 5, 14, 15, 16,17,18)
- export to One-Click-Connection XAUTH, L2TP

- Ste-to-site
  Client-to-Site (Road warrior)
  Routing-Mode-VPN
  Bridge-Mode-VPN
  X.509-certificates
  TCP/UDP port changeable
  Compression
  specify WINS- and DNS-servers
  3DES, AES (128, 192, 256)
  CAST5, Blowfish
  Export to One-Click-Connection

# Windows-PPTP compatible Specify WINS- and DNS-servers MSCHAPv2

**▶ VPN-client** 

- X.509 certificates CRI
- OCSP
- Templates
- Multi CA support Multi host-cert. support
- IPSec-client
- SSL-client (OpenVPN) NAT-T IVAI-1 AES (128, 192, 256), 3DES CAST, Blowfish X.509 certificates PSK

### One-Click-Connection Log-export

- **▶** Command Center
- eGUI Technology, ISO 9241 compliant Monitor 500+ firewalls Active configuration of 500+ firewalls VPN connections centrally creatable
- Single- and group-backup
  Plan automatic backup in groups
  Single- and group update & licensing
  Create and apply templates on multiple
  firewalls
  Catificate beand 4006 bit preparated
- Certificate based 4096 bit encrypted
- connections to the firewalls
  Display settings of all firewalls
  Role based command center user
- management VPN-monitoring
- \* Not available in the GPO75/GPO75a