

DrayTek

VigorSwitch P1090

8-Port PoE Gigabit Switch

- 8-Port PoE Gigabit Switch
- Port 1-4 support 802.3at PoE+ (Up to 30W power)
- 150 Watts total PoE Power (15.4W/port)
- Quality Internal PSU (mains powered)
- 11" Metal Case
- Support Rack-mount brackets
- Zero Configuration

The DrayTek VigorSwitch P1090 switch, an 8-port Gigabit switch offers full-power to all these ports with Power of Ethernet (PoE) capability. All PoE-enabled devices for the business usages, such as IP phones (e.g. VigorPhone series), wireless access points (e.g. VigorAP series) or IP Cameras can all rely on VigorSwitch P1090 switch for the power supply to ease the deployment difficulties.

With DrayTek VigorSwitch P1090 switch, you are free to position equipments wherever they should be and power to the unit with the data over the Ethernet cable, not being limited by the power outlet. You can remotely reboot the device without having to climb up to or go to the device - just remove its Ethernet cable from the switch end as adopting PoE.

All ports of VigorSwitch P1090 switch are auto-sensing that make each port only provides power as detecting the presence of an 802.3af/at PoE device. In other words, VigorSwitch P1090 switch saves power and prevents compatibility issues or possible damage/hazard.

In short, VigorSwitch P1090 can simultaneously deliver the stable power supply to all 8 ports without overload or power being reduced on any of it and is also well-engineered to be reliable and maintenance free. The VigorSwitch P1090 can be rack mounted or operated on a desk/shelf.

You can establish the ideal IP office based on the advance IPPBX devices with comprehensive VPN and firewall features (e.g. VigorIPPBX 2820 series and VigorIPPBX 3510). As deploying IP extensions for your employees and IP cameras for surveillance needs, you can adopt VigorSwitch P1090 to enhance the workplace productivity and security by the easy installation.



Technical Specifications

Standards	IEEE 802.3 10Base-TX IEEE 802.3u 100Base-TX IEEE 802.3ab 1000Base-TX IEEE 802.3x Flow Control IEEE 802.3af IEEE 802.3at
Features	Number of Ports: 8 PSE/Power over Ethernet Ports, Port 1-4 Support PoE+ MAC Address: 8K Buffer Memory: 128KB Transmission Method: Store and Forward Support Loop Detection Wire-speed Packet Filtering and Forwarding Rate
Led Indicators	Per Port: Link/Act (Green) Per Unit: Power (Green) Loop Detection: Red
Power Input	100~240V/AC, 50~60Hz
Power Consumption	150 Watts (Max)
Dimensions	262 × 184 × 41 mm (L x W x H)
Weight	1.4 kg
Operating Temperature	0 to 40°C
Storage Temperature	-20 to 90°C
Humidity	10 to 90% RH (non-condensing)
Certifications	FCC Class B, CE

