



## OVERVIEW

**SI0802GP** is a full Gigabit managed industrial PoE fiber switch independently developed by XENTINO. It has **8\*10/100/1000M PoE** ports and **2\*100/1000M SFP** fiber ports. Port 1-8 can support IEEE802.3af/at standard POE, single port POE power up to 30W. As a POE power supply device, it can automatically detect and identify the electrical equipment that meets the standard and supply power through the cable. It can supply the POE terminal equipment, such as wireless AP, network camera, network telephone, industrial sensor and so on, to meet the demand for high density PoE power supply network environment. It is suitable for intelligent transportation, rail transit, electric power, mining, metallurgy and green energy. Industrial scenes such as construction set up a cost-effective and stable communication network.

The **SI0802GP** has L2+ network management function, support IPV4 management, static route full line rate forwarding, security protection mechanism, ACL/QoS policy and VLAN, and is easy to manage and maintain. Support multiple network redundancy protocols STP/RSTP/MSTP(<50ms) to improve link backup and network reliability. When one-way network fails, communication can be quickly restored to ensure important Uninterrupted communication for applications. According to the actual application requirements, you can configure multiple application services such as PoE power management, port traffic control, VLAN division, and SNMP through the Web network management mode.

## FEATURES

### ❖ Gigabit wire speed forwarding

- Support Gigabit Ethernet port and Gigabit SFP port combination, which enables users to flexibly build networking to meet the needs of various scenarios.
- Support non-blocking wire-speed forwarding.
- Support full-duplex based on IEEE802.3x and half-duplex based on backpressure.

### ❖ Powerful port lightning protection, ultra-wide voltage input

- Contact discharge 8KV, air discharge 15KV, port lightning protection common-mode 4KV, differential mode 2KV
- Industrial dual power input
- DC INPUT: 48V-57V

### ❖ Intelligent PoE power supply

- 8\*10/100/1000Base-T RJ45 ports, meeting the needs of security monitoring, teleconferencing system, wireless coverage, and other scenarios.
- IEEE802.3af/at PoE standard, without damaging non-PoE devices.

- Priority system for PoE port, it will supply power to the high priority level port first when the power budget is insufficient and avoid overwork of the device.
  - PoE network management, realize PoE port power allocation, priority setting, port power status viewing, time scheduling, etc.
- ❖ **PoE network management and fast Ring function**
- IEEE802.1Q VLAN, flexible VLAN division and QinQ configuration.
  - QoS, Priority mode based on 802.1P, Port & DSCP, queue scheduling algorithm including EQU, SP, WRR & SP+WRR.
  - ALC, filter data packet through configuring matching rules, processing operation & time permission, and provide flexible and safe access control.
  - IGMP V1/V2 and IGMP Snooping.
  - STP/RSTP/MSTP.
  - Static and dynamic aggregation.
- ❖ **Security**
- 802.1X authentication.
  - Port isolation, Storm control.
  - IP-MAC-VLAN-Port binding.
- ❖ **Stable and reliable**
- Low power consumption, aluminum shell. No fan.
  - CCC, CE, FCC, RoHS.
  - The user-friendly panel, it can show the device status through the LED indicator of PWR, SYS, Link, L/A, PoE.
- ❖ **One-stop remote control and management**
- Web management, CLI command line (Console, Telnet), SNMP (V1/V2/V3).
  - HTTPS, SSLV3, and SSHV1/V2.
  - RMON, system log, LLDP, and port traffic statistics.
  - CPU monitoring, memory monitoring, Ping test, and cable diagnose.


## TECHNICAL SPECIFICATION

XENTINO SI0802GP	
<b>Interface Characteristics</b>	
Fixed Port	8*10/100/1000Base-T PoE ports (Data/Power) 2*100/1000Base-X uplink SFP slot ports (Data) 1 * RS232 console port(115200, N, 8, 1) 2 set of V+, V- redundant DC power interface (5 Pin Phoenix terminal)
Ethernet Port	Port 1-8 support 10/100/1000Base-T, auto-sensing, Full/half duplex MDI/MDI-X self-adaption
Twisted Pair Transmission	10BASE-T: Cat3,4,5 UTP(≤100 meter) 100BASE-TX: Cat5 or later UTP(≤100 meter) 1000BASE-T: Cat5e or later UTP(≤100 meter)
SFP Slot Port	Gigabit SFP optical fiber interface, default matching optical modules (optional order single-mode / multi-mode, single fiber / dual fiber optical module. LC)
Optical Cable/Distance	Multi-mode: 850nm/0 ~ 550M, single-mode: 1310nm/0 ~ 40KM, 1550nm/0 ~ 120KM.
<b>Chip Parameter</b>	

Network Protocol	IEEE802.3 10BASE-T, IEEE802.3i 10Base-T, IEEE802.3u 100Base-TX IEEE802.3ab 1000Base-TX, IEEE802.3z 1000Base-X, IEEE802.3x
Forwarding Mode	Store and Forward(Full Wire Speed)
Switching Capacity	128Gbps (Non-blocking)
Forwarding Rate	14.88Mpps (@64byte)
MAC	8K
Buffer Memory	4.1M
Jumbo Frame	10K
LED Indicator	Power: PWR (Green), System: SYS (Green), Network: Link (Yellow), Fiber port: L/A (Green), PoE: PoE (Green)
Reset Switch	Yes. Press and hold the reset switch for 10 seconds and release it to restore factory settings
<b>PoE &amp; Power Supply</b>	
PoE Port	Port 1 to port 8
PoE Management	PoE working status Delay start of power supply PoE output priority configuration Scheduling of PoE operation and time Total power limit of PoE power supply PoE output power allocation, off& af &at
Power Supply Pin	1/2 (+), 3/6 (-)
Max Power Per Port	30W, IEEE802.3af/at
Total PWR / Input Voltage	120W/48VDC
Power Consumption	Standby<8W, Full load<120W
Power Supply	No, optional 48V/120W or 48V/240W industrial power supply
Working Voltage	48-57VDC, 5P industrial phoenix terminal, anti-reverse protection
<b>Physical Parameter</b>	
Operation TEMP / Humidity	-20~+55°C, 5%~90% RH Non condensing
Storage TEMP / Humidity	-40~+75°C, 5%~95% RH Non condensing
Dimension	165*148*54mm (L*W*H)
Net /Gross Weight	<0.8kg / <1.2kg
Form Factor	Desktop, DIN rail mounting
<b>Certification &amp; Warranty</b>	
Lightning Protection / Protection Level	Lightning protection: 6KV 8/20us; Protection level: IP40 IEC61000-4-2(ESD): ±8kV contact discharge, ±15kV air discharge IEC61000-4-3(RS):10V/m(80~1000MHz) IEC61000-4-4(EFT): power cable: ±4kV; data cable: ±2kV IEC61000-4-5(Surge): power cable:CM±4kV/DM±2kV; data cable: ±4kV IEC61000-4-6(radio frequency transmission):10V(150kHz~80MHz) IEC61000-4-8(power frequency magnetic field):100A/m;1000A/m ,1s to 3s IEC61000-4-9(pulsed magnet field):1000A/m IEC61000-4-10(damped oscillation):30A/ 1MHz IEC61000-4-12/18(shockwave):CM 2.5kV, DM 1kV IEC61000-4-16(common-mode transmission):30V; 300V,1s FCC Part 15/CISPR22(EN55022): Class BIEC61000-6-2(Common Industrial Standard

Mechanical Properties	IEC60068-2-6 (anti vibration), IEC60068-2-27 (anti shock) IEC60068-2-32 (free fall)
Certification	CCC; CE mark, commercial; CE/LVD EN60950; FCC Part 15 Class B;
Warranty	2 years, lifelong maintenance.
<b>Network Management Features</b>	
Interface	IEEE802.3X (Full-duplex) Port temperature protection setting Port green Ethernet Energy-saving setting Broadcast storm control based on port speed The speed limit of the message flow in the access port. The minimum particle size is 64Kbps.
Layer 3 Features	L2+ network management, IPV4 management Static route, Default route @ 128 pcs, APR @ 1024 pcs
VLAN	4K VLAN based on port, IEEE802.1q VLAN based on the protocol, VLAN based on MAC QinQ configuration, Port configuration of Access, Trunk, Hybrid
Port Aggregation	LACP, Static aggregation, Max 5 aggregation groups and 8 ports per group.
Spanning Tree	STP (IEEE802.1d),RSTP (IEEE802.1w),MSTP (IEEE802.1s)
Industrial Ring Network Protocol	250 Ring at most, Max 250 devices per ring.
Multicast	MLD Snooping v1/v2, Multicast VLAN IGMP Snooping v1/v2, Max 1024 multicast groups, Fast log out
Port Mirroring	Bidirectional data mirroring based on port
QoS	Flow-based Rate Limiting Flow-based Packet Filtering 8*Output queues of each port 802.1p/DSCP priority mapping Diff-Serv QoS, Priority Mark/Remark Queue Scheduling Algorithm (SP, WRR, SP+WRR)
ACL	Port-based Issuing ACL, ACL based on port and VLAN L2 to L4 packet filtering, matching first 80 bytes message. Provide ACL based on MAC, Destination MAC address, IP Source, Destination IP, IP Protocol Type, TCP/UDP Port, TCP/UDP Port Range, and VLAN, etc.
Security	IP-MAC-VLAN-Port binding ARP inspection, Anti-DoS attack AAA & RADIUS, MAC learning limit Mac black holes, IP source protection IEEE802.1X & MAC address authentication Broadcast storm control, Backup for host datum SSH 2.0, SSL, Port isolation, ARP message speed limit User hierarchical management and password protection
DHCP	DHCP Client, DHCP Snooping, DHCP Server, DHCP Relay
Management	One-key recovery Cable Diagnose, LLDP Web Management (HTTPS) NTP, System work log, Ping Test CPU instant utilization status view Console/AUX Modem/Telnet/SSH2.0 CLI Download & Management on FTP, TFTP, Xmodem, SFTP, SNMP V1/V2C/V3
System	Category 5 Ethernet network cable Web browser: Mozilla Firefox 2.5 or higher, Google browser chrome V42 or higher, Microsoft Internet Explorer10 or later; TCP/IP, network adapter, and network operating system (such as Microsoft Windows, Linux, or Mac OS X) installed on each computer in a network

## DIMENSION



## ORDERING INFORMATION

Model	Description	Recommended Power Supply
SI0802GP	L2+ managed industrial PoE fiber switch with 8*10/100/1000M RJ45 ports and 2*100/1000M SFP ports, Port 1-8 can support IEEE802.3af/at PoE. Support dual DC power supply input and DIN rail mounting.	120W/240W

**Note:** The industrial PoE switch not including SFP optical module and power supply. and

## PACKAGE CONTENT

QTY	UNIT	CONTENT
1	SET	10-port full gigabit managed industrial PoE switch
1	PC	RJ45-DB9 Line
1	PC	User Guide
1	PC	Warranty Card