D16000 JBOD Subsystem



D16000 miniSAS (x4) to SAS/SATA 6G (x16) JBOD Sybsystem

Specification

-RAID Controller: JBOD Single Controller

-Host Interface: One 4x miniSAS (6Gb/s)

-Expansion Interface: One 4x miniSAS (6Gb/s)

-DAS Expansion: Allows 2 DAS to be added to each of the two ports available on the HBA Host card, for a total of 4 DAS. Up to 64 Disks.

-Disk of status indicators:Power, Activity, Error -Disk Interface: SAS/SATA 6G -No of Drivers: 16 (SAS/SATA) -Power Supply: 500W Redundant power supply (80plus)
-System Fan: Hot swappable (x2)
-Environment: Temperature: 5°C to 40°C Humidity: 0 ~ 80 % R.H. (Non-condensing)
-Chassis: 3U Rack mount
-Dimensions (HxWxD): 130 x 480 x 518 (mm)
-Weight: 25.96Kgs

<image><section-header><text><text>



Thecus[®] HO

15F., No.79, Sec. 1, Sintai 5th Rd., Sijhih Dist,

New Taipei City 221, Taiwan (R.O.C.)

Forum: forum.thecus.com

Email: sales@thecus.com Facebook: www.facebook.com/Thecus

Twitter: twitter.com/Thecus_Storage RSS: www.thecus.com/rss_news.php Youtube: www.youtube.com/thecusstorage

Thecus[®], Creator in Storage

www.thecus.com

Thecus® U.S.A., Inc.

487 Montague Expressway, Milpitas, CA 95035, USA Email: support@us.thecus.com Tech support: ussupport.thecus.com/esupport

Thecus[®] NL B.V.

Marinus Dammeweg 7, 5928 PW Venlo, the Netherlands Email: thecus_nl@thecus.com Tech support: esupport.thecus-eu.com Support e-mail: support_nl@thecus.com

Thecus[®] Germany

Siemensstr. 17, 76275 Ettlingen Email: support@thecus-service.de Tech support: esupport.thecus-eu.com

\cdot Massive expansion with effortless and affordable daisy-chaining